



UDC900 2W

902-928 MHz

The Up/Down Converter 900 2W

A highly linear product that delivers 2 Watt of 900 MHz signal for long range applications. Outdoor unit delivers full power right at the antenna feed. Works with all brands of 2.4GHz radios without any adjustments, including Direct Sequence (DSSS).

Also available in OEM package with 12VDC input for use within an existing 2.4GHz radio. Contact sales office for details.



902-928 MHz 2W
Item# 13-106

Technical Specification

Frequency Band to Antenna	902 - 928 MHz
Frequency Band to Radio	2438 - 2464 MHz
Local Oscillator Frequency	1536 MHz
Frequency Stability	+/- 2.5 ppm
Output Power (3.4 GHz)	2 Watt (+ 33±dBm)
Input Power (2.4 GHz)	10 mW ~ 50 mW(10 dBm to 17 dBm)
Tx Conversion Gain	up to 22 dB
RF Connector	N-Type, female, 50 Ohm
Rx Conversion Gain	15 dB
Noise Figure	4 dB
Power Consumption	12 VDC @ 1.8 A or 105 ~ 240 VAC for power supply (kit provided)
Operating Temperature	-40 °C to + 70 °C
Dimensions	6.00" L x 3.75" W x 1.25" H