

Introducing Teletronics' TT™X Series





- Powerful QoS for Real Time Applications
- Dynamic Bandwidth Control Management
- Ruggedized waterproof and all weather enclosure
- WDS available in AP Mode

Specifications

Standard Compliance: IEEE 802.11a

Modulation: OFDM w/BPSK, QPSK, 16 QAM, 64 QAM Modulation

Frequency Band: 5.725 - 5.850 GHz (US FCC) 5.15 - 5.825 (Available ONLY for OEM, Military & Export Version)

Data Rate: 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, and 1 Mbps

Output Power: 19 dBm (+/- 3dB) @ 6/9/12 /18/24 Mbps, 18 dBm @ 36 Mbps, 17 dBm @ 48 Mbps, 16 dBm @ 54 Mbps

Mounting: For both wall and pole mount

Enclosure: Powder Coated Cast Aluminum

Connector: N-Type Female

Receive Sensitivity: -87 dBm ≤ 6 Mbps

Item# 11-177 (AP Gateway)

Item# 11-178 (SU Gateway)

Ultra High 500mW Output power in

Web & SNMP based Management

Adjustable Transmit (TX) Power

Intra-BSS Traffic Blocking

Configurable ACK timeout

(Layer 2 Isolation)

for long distance

Turbo-mode for high

data rate (108 Mbps)

OFDM modulation (w/optional M58 amp)

FCC ID: MFMTT5800

Features

EZManager

-70 dBm ≤ 54 Mbps RF Channels:

Total of 13 Non-Overlapping Ch. (5 Channels: 5.725 ~ 5.850 GHz)

Data Security: WPA, WPA2 & 64/128 bit WEP Data Security, MAC Address Filter, Intra-BSS Traffic Blocking (Layer 2 Isolation)

Management: Web and SNMP based Management EZManager

Ethernet Connection: 10/100 Base T Auto MDI/MDX

DC Power Input:

Includes 48VDC Adapter & PoE Injector with surge protection IEEE 802.3af compliant

Operating Temperature: -40 °C to + 70 °C Weight: 5.5 lbs

TT™5800X Special Features:

WAN:

- Static IP/DHCP Client/PPPoE Client
- MAC Cloning
- WAN Ping Inbound Filter

LAN:

- RIP Support
- DNS Relay
- DHCP Server including IP-MAC Reservation

WIRELESS:

- SSID Hiding
- WEP/WPA/WPA2 Enterprise
- MAC Filtering
- WDS
- 802.11d
- RTS/Fragmentation Threshold
- Ack Timeout
- Transmit Power
- Auto Channel Select

GATEWAY:

- NAT
- UPNP NAT Passthrough
- Firewall/DMZ (Demilitarized Zone)
- QoS (Bandwidth Control)

MANAGEMENT:

- Syslog
- Ping Watchdog
- Firmware Upgradeable
- Configuration Import/Export
- EZ Manager